JACKET:
- SOOW CABLE
- 3 CONDUCTOR, 16 AWG
- TEMPERATURE RANGE: −40°C TO 90°C

INDUSTRY APPROVALS:
- UL FLEXIBLE CORD UL SUBJECT 62
- CSA FLEXIBLE CORD C22.2−49
- MSHA APPROVED
- ROHS COMPLIANT

- MILITARY STANDARD
- 3106 STYLE
- INSERT ARRANGEMENT 18−11S
- SOLID BACKSHELL
- MAX DIAMETER 1.22 IN.





CONNECTOR PIN	FUNCTION	CONNECTOR COLOR	CONNECTOR TYPE
C	CLOSE	GREEN	#16 AWG 26/30 STRAND
D	OPEN	BLACK	#16 AWG 26/30 STRAND
B	COMMON	WHITE	#16 AWG 26/30 STRAND

REV. NO.	DATE	APPROVAL	DESCRIPTION
A	11/6/13	D.HAMILTON	INITIAL DRAFT

SEL SCHWEITZER ENGINEERING LABORATORIES
PULLMAN WASHINGTON USA

This drawing was prepared for a specific project by SEL. Use of this drawing for any other purpose is prohibited unless written permission is provided by SEL and the customer.

C526

CABLE, CONTROL, JUNCTION BOX, 5−PIN

SCALE NTS | ENGINEER S. COLLIGAN | DRAFTER D. HAMILTON | DATE 11/6/13

DWG NO. LDWC526 | SHT 1 OF 1 | REV A