

SEL-WA05010W, WA05510W

Wiring Harness for SEL 500-Series
Connectorized® Relays
Features New Shorting Connector



2350 NE Hopkins Court • Pullman, WA 99163-5603 USA
Phone: (509) 332-1890 • Fax: (509) 332-7990
Internet: www.selinc.com • E-mail: info@selinc.com

Ordering Information

Part Number Example: WA05010WBX2A

For SEL-501, SEL-587 Connectorized***

W A 0 5 0 1 0 W

	X		A
--	----------	--	----------

For SEL-551 Connectorized***

W A 0 5 5 1 0 W

	X		A
--	----------	--	----------

Choose from the options below. Enter option codes to complete the appropriate part number.

Wire Size for Current Inputs

#10	A			
#12**	B			
#14	C			
#16	D			

Wire Length

4 feet				1
8 feet**				2
12 feet				3
16 feet				4
20 feet				5
>20 feet				0

Wire Type

XLP** (Wire Insulation: Crosslinked Polyethylene (XLP); Temp. Range: -40° to 90°C; Voltage Rating: 600 Volts)				A
--	--	--	--	----------

* = Additional Cost.

** = Standard options. Specify part number WA05010WBX2A or, WA05510WBX2A.

*** = To order test harness, specify part number WA05010W or WA05510W.

- Wire Length: 6 inches
- Terminated with banana jacks
- No wire options